

2024 Rungu Dualie® Model Specifications

Models	Standard	Steep	Rugged	XR Steep	XR Rubicon Trail Edition
Motor	Bafang BBShD 52V Mid-Drive with 5 level power output				
Power Output	Nominal 1,120 W (Max 1,429W)				
Max Rear Wheel Torque	276 Nm		328 Nm	276 Nm	328 Nm
Battery (52V)	830 Wh	830 Wh	1,000 Wh	Dual 936 Wh (1,872 Wh)	Dual 936 Wh (1,872 Wh)
Off-road range¹	21 mi (34 km)	21 mi (34 km)	24 mi (38 km)	43 mi (70 km)	42 mi (67 km)
MAX Gravel/On-Road Range²	123 mi (199 km)	120 mi (192 km)	135 mi (217 km)	247 mi (397 km)	235 mi (378 km)
Minimum Rider Height	5'				
Max Rider Height w/o Steering Risers	6' 3"				
Max Rider Height with Steering Risers	6' 9"				
Frame Type	Rungu Dualie Integrated	Rungu Dualie Integrated and Reinforced	Rungu Dualie Integrated and Reinforced	Rungu Dualie Non-Integrated	Rungu Dualie Non-Integrated
Suspension	Dual front shock - 100 mm travel				
Standard Gearing	Microshift Advent 9 Speed	Microshift Advent 9 Speed wth Indicator	Box Prime 9 with Rungu Gear Shield	Microshift Advent 9 Speed wth Indicator	Box Prime 9 with Rungu Gear Shield
Load Capacity	350 lbs. (159 kg)	344 lbs. (156 kg)	335 lbs. (152 kg)	332 lbs. (151 kg)	321 lbs. (151 kg)
Off-road top speed³	24 mph (38 kph)	24 mph (38 kph)	24 mph (38 kph)	23 mph (37 kph)	23 mph (37 kph)
Front Tires (dual)	Vee Rubber Snow Avalanche 26 x 4.8"	Vee Rubber Snow Avalanche 26 x 4.8"	Maxxis Minion FBF 26 x 4.8" with Tannus Armour Liners	Vee Rubber Snow Avalanche 26 x 4.8"	Maxxis Minion FBF 26 x 4.8" with Tannus Armour Liners
Rear Tire	Vee Rubber SnowShoe XL 26 x 4.8"	Vee Rubber SnowShoe XL 26 x 4.8"	Maxxis Minion FBR 26 x 4.8" with Tannus Armour Liner	Vee Rubber SnowShoe XL 26 x 4.8" with Tannus Armour Liner	Maxxis Minion FBR 26 x 4.8" with Tannus Armour Liner
Accessories Included	Dual Front Mud Guards with Diverter, Seat Post Mounted Rear Fender, 6W headlight	Dual Front Mud Guards with Diverter, 6W headlight, Heavy Duty Cargo Rack	Dual Front Mud Guards with Diverter, 6W Headlight, Heavy Duty Cargo Rack with waterproof panniers and mounts, Skid Plate, Tire Inflator, Spare chain and tube, Tools, Spare Fasteners	Dual Front Fenders, 36W headlight, Heavy Duty Cargo Rack with Battery Case	Dual Front Fenders, 36W headlight, Heavy Duty Cargo Rack with Battery Case with waterproof panniers and mounts, Skid Plate, Tire Inflator, Spare chain and tube, Tools, Spare Fasteners

¹ Estimate based Rungu carrying 175 lbs. load, on flat ground, no wind, tire pressure appropriate for ground, no stops/starts traveling at average 10 mph. Battery operating between 40 and 90 degrees fahrenheit.

² Estimate based maximum range for Rungu carrying 175 lbs. load, on flat ground, no wind, no stops/starts traveling at 10mph. We assume an average of 50W of power contribution from the rider when using pedal assist. Battery operating between 40 and 90 degrees fahrenheit.

³ Throttle-only speed for 175 lb. load, on flat dirt road, with no wind. Actual top speed may differ.

Don't see what you're looking for - contact sales@riderungu.com for a full set of detailed specifications