



RUNGU DUALIE®

STEEP



Stealth ATV Advantages

- **Rungu Dualie's Double Wheel Design**, two front wheels spaced 9 inches apart, makes riding much safer as it virtually eliminates the washouts and over-the-bar wipeouts common with any single-wheel E-Bike, Bike or Moto off-road. The Double Wheel Design provides ATV-like off-road control without the inherent roll-over danger of an ATV or the noise!
- Like a Quad ATV, Rungu Dualie **muscles through where other E-Bikes cannot**. With up to 204 ft. lbs. of torque, Rungu Dualie Steep conquers soft sand, **snow (up to 9 inches or more)**, mud, rocks, logs. With that torque and the trailer hitch option or one of our trailers, you can **pull up to 300 lbs.**¹
- Patented form of Ackerman Steering, which results in smooth off-road control. **The two front wheels grip terrain like a Quad ATV or a 4WD Jeep.**
- **Climbs much steeper terrain** without getting out of the saddle. Rungu Dualie's center of gravity is further forward keeping you in the saddle at grades over 40%.
- With more distance between you and the front wheels and twice the braking power compared to a conventional off-road E-Bike, Rungu Dualie **descends steep terrain safer and with much more control.**
- Rungu Dualie's modified step-through frame supports up to 350 lbs. without compromising a **26.5-inch standover height**. Nobody likes standing on their tiptoes to avoid a crotch crunch.

Specifications

- Length – wheelbase 54.7 in. | projected length 85 in.
- Width – handlebar width 32.7 in. | Path width (distance from outside of one front tire to the other) 13.75 in.
- Weight – 91 lbs.
- Frame size - 14.5 in.
- Saddle surface height – lowest position 34 in., highest position 42 in.
- Stand-over height - 26.5 in.
- Ground clearance – 10 in.
- Max. Combined Load weight - 347 lbs.

Performance

- Estimated range – off-road with pedal assist² - up to 21 mi @ 10 mph | on pavement with pedal assist – up to 122 mi @ 10 mph
- Max climbing grade³ - up to 47%
- Top speed off-road – up to 24 mph⁴
- Max power output – 1429 W⁵ (1.9 Hp)
- Max torque at rear wheel – 223 ft-lb⁶

Factory Configured Options

- Color - Available in Midnight Black, Forest Green (as shown) or Winter Slate and Premium Colors: Sitka Spruce, Carbon Stealth, and Sandstone Wash
- Custom Powder Coat or Camo wrap
- 3/8" Skid Plate upgrade
- Upgrade option - 2" Ball Hitch on Cargo Rack - Max Towing Weight 300 lbs.

Warranty

- 2-year on all components, details in Sales Terms and Conditions document

"I bought my Rungu Dualie Steep in April '22 and I've been riding it every weekend since. I've put it to the test riding way too fast and way outside my comfort zone, but this bike is a tank! I love it. I was only going to hunt with the Rungu Dualie, but now it's my favorite toy!" – Jordan E., Rungu Dualie Customer

¹ See YouTube video: [Rungu Dualie Rungu Dualie Single Speed Truck Tow Demo](#)

² Estimate based on experience and calculation of maximum range for Rungu carrying 175 lbs. load, on flat ground, no wind, no stops/starts traveling at speed indicated for Max Range. We assume an average of 50W of power contribution from the rider when using pedal assist. Battery operating between 40° and 60° Fahrenheit.

³ Based on experience and calculations. Conditions include load limited to 175 lbs., hard surface, speed of 3 mph and slope distance of 50 ft. Actual maximum climbing grade may differ.

⁴ Based on experience and calculations. Throttle-only speed for 175 lb. load, on flat dirt road, with no wind. Actual top speed may differ.

⁵ At full charge of 58.8V, 33A input at 121 rpm output

⁶ At lowest gear ratio for MicroSHIFT Advent gearing 1:1.53

Model Features⁷

Category	Feature ↓ Model →	Dualie Standard	Dualie Steep	Dualie Rugged	Dualie XR Steep	Dualie XR Rugged
Drivetrain	Rungu-designed 6061-T6 Aircraft Aluminum, hand welded frame. Integrated Battery design with key-lock battery access.	*	*	*	*	*
	Patented dual-handlebar steering assembly with sealed bearing alloy headset with soft-impact handlebar end-stops	*	*	*	*	*
	Bafang BBSHD 1120W mid-drive motor with 52V modification - color digital display with USB power outlet, thumb throttle and control pad. Top power output of 1.9 Hp.	*	*	*	*	*
	High strength alloy 30T chainring	*	*	*	*	*
	microSHIFT Advent 9 Speed gear change system - derailleur with clutch mechanism, trigger shifter and wide range (11-42T) cassette. High-strength chain designed for e-bikes. Gearsensor.com electronic clutch to reduce risk of chain-snap during gear changes	*				
	microSHIFT Advent 9 Speed gear change system - derailleur with clutch mechanism, trigger shifter and wide range (11-46T) cassette. High-strength chain designed for e-bikes. Gearsensor.com electronic clutch to reduce risk of chain-snap during gear changes		*		*	
	BOX Prime 9 gear change system - derailleur with clutch mechanism, "Push-Push" trigger shifter and extra wide range (12-50T) cassette. High-strength chain designed for e-bikes. Gearsensor.com electronic clutch to reduce risk of chain-snap during gear changes.	U	U	*	U	*
	Rohloff Speed Hub internally geared hub 14 speed. Gearsensor.com electronic clutch to reduce risk of transmission damage during gear changes.	U	U	U	U	U
	Wheelset: 26" alloy rims designed for fat tires with stainless steel spokes and sealed-bearing alloy hubs	*	*	*	*	*
	Tires: Maxxis Minion 4.8" x 26", presta valve inner tube	*	*	*	*	*
Battery system	Rear tire Tannus Armour Liner	U	U	*	*	*
	Front tires - Dual Tannus Armour liners	U	U	*	U	*
	Mesquite-Proof Tire Liners - All tires	U	U	U	U	U
	Rungu Integrated 52V 16 Ah (832 Wh) LINC battery with built-in remaining charge indicator, charging port and USB power output	*	*			
	Rungu Integrated 52V 19.3 Ah (1,000 Wh) LINC battery with built-in remaining charge indicator, charging port and USB power output	U	U	*		
	Dual Rungu Integrated 52V 16 Ah (832 Wh) LINC batteries with built-in remaining charge indicator, charging port and USB power output		U		*	
	Dual Rungu Integrated 52V 19.3 Ah (1,000 Wh) LINC batteries with built-in remaining charge indicator, charging port and USB power output		U			*
	4A battery charger - full charge in less than four (4) hours	*	*	*	*	*
	Off-road grips	*	*		*	
	ODI performance off-road grips			*		*
Comfort	Rungu custom GTMRK fat tire suspension forks with 100 mm travel, adjustable coil tension and lock out	*	*	*	*	*
	Extra comfort Velo® Plush Gel saddle and 400 mm alloy seat post, alloy quick release adjustment clamp	*	*	*	*	*
	Serfas Full Suspension Cruiser Saddle	A	A	A	A	A
	Cirrus Cycles Kinekt XR/LR - suspension seat post up to 320 lb. rating	A	A	A	A	A
	Dual quad-piston hydraulic front disc brakes with parking brake and 203mm rotors. Electronically integrated with motor.			*	*	*
	Dual hydraulic front disc brakes with parking brake and 203mm rotors. Electronically integrated with motor.	*	*		*	*
	Rear, quad-piston hydraulic rear brake with 203mm rotor. Electronically integrated with motor.	*	*	*	*	*
	Rear, quad-piston hydraulic rear brake with 180mm rotor. Electronically integrated with motor.	*	*	*	*	*
	Rungu integrated headlight	*	*	*	*	*
	Rechargeable/removable taillight with brake-sensing technology	A	A	A	A	A
Safety	Front mudguards with Mud Diverters	A	*	*	*	*
	Seatpost mounted rear fender	A				
	3/8" UHMW Skid Plate/bash guard	U	U	*	U	*
	Aluminum Anodized Chainguard	*	*	*	*	*
	Rungu Cargo Rack - NEW lighter-weight welded design	A	*	*	*	*
	Rungu Spare Battery Carrier for use with Rungu Cargo Rack		U	U	*	*
	Cargo Trailer or Deer Cart	U	U	U	U	U
	Front Cargo Rack	A	A	A	A	A
	Cell-Phone Mount	A	A	A	A	A
	Rungu Heavy Duty Kickstand for off-center loads and off-road parking		A	A	A	A
Accessories	Rungu Tool Bag, Hex wrenches - set of 10 + Presta-schrader converter valve converters	*	*	*	*	*
	Rungu Gear Shield - keep sticks, weeds and grasses out of derailleur and cassette	A	A	*	A	*
	Dual Pannier setup		A	*	A	*
	Cycplus pump with adapter and spare tube and first aid kit			*		*
	spare chain, combo chain removal tool and tire levers			*		*
	Off-road only - full power (Max 1429 W output)	*	*	*	*	*
	Optional Class 1 or Class 2 configuration (Max 750W output)	O	O	O	O	O
	Canadian configuration (Max 500W output)	O	O	O	O	O
	Midnight Black	O	O	O	O	O
	Winter Slate	O	O	O	O	O
Color	Forest Green	O	O	O	O	O
	Sitka Spruce		U	U	U	U
	Carbon Stealth		U	U	U	U
	Sandstone Wash		U	U	U	U
	Custom Powder Coat	U	U	U	U	U
	Custom Camo wrap	U	U	U	U	U

* = Included

A = Accessory/After sale upgrade item

O = Factory configured option - no additional charge

U = Factory configure upgrade - additional charges. Additional lead time applies for upgrade colors and Rohloff transmission.

Selected Accessories



Rungu® Deer Cart

Pull loads of up to 220 lbs. without the need of a ball hitch. Collapses so you can carry on rack and deploy when you need it.



Rungu Gear Shield

Protect your derailleur and cassette from entanglement and damage by weeds, sticks and tall grasses.

Rungu and Rungu Dualie are registered trademarks of Standard Bearer Machines, LLC. We make every Rungu Dualie in the USA from domestic and imported parts. Copyright 2026. For more information visit www.rungudualie.com

⁷ Specifications, components, and other details subject to change without notice